

SPTK-FTTH-03C

FTTH Tool Kits



NO.	Name	
1	Fiber Cleaver	
2	Optical PowerMeter-70 to+l0dBm	
3	Visual Fault Locator 5km	
4	Drop Cable Stripper	
5	CFS-2 Fiber Optic Stripper	
6	Tool Kits Carrying Bag	
7	Alcohol Bottle	
8	Kevlar Scissors	
9	SC for Power Meter	
10	Cleaver box	

Product Parameter



Tool kit

- 1. Thick cotton pad compartment to protect equipment
- 2. Equipped with a strap for carrying and carrying



Push alcohol bottle

- 1. Suitable for cotton balls, wipes, etc
- 2.Not volatile
- 3. Prevent corrosion and overflow With anti-blowout function
- 4. The solution oozes out at the touch of a button



Wire stripper

- 1.Reinforced type with graduation, can cut the steel wire in the leather thread
- 2.Suitable for 3.1mm*2.0mm leather cable
- 3. Cuttable plastic reinforced metal core
- 4.Used for twisted pair, tight-clad cable, CATV cable





Miller stripper

- 1. Easy to scratch the coating, no damage to the bare fiber
- 2. Can strip 125mm fiber loose tube. bare fiber. sheathed fiber
- 3. Adjustable bite
- 4.Length 165.cm, weight 0.15KG



Kevlar Scissors

- 1.Serrated design of cutting edge can effectively eliminate slippage when shearing Kevlar wire.
- 2. The handle is made of elastic plastic.

Dexterous and easy to hold and operate. Specially designed for shearing the outer layer of optical fiber.

- 3.Long service life
- 4.Length 14cm



Red light pen

- 1. The body is made of metal to prevent damage
- 2. This red light pen uses a laser head
- 3. Easily penetrate fiber Easy to carry and feel comfortable
- 4. Stable performance, strong light source



W1	200 1600
Wavelength Range (nm)	800~1600
Detector lype	InGaAs
Measurement Range(dBm)	-50~+26
Uncertainty 3	+0.15dB
Accuracy	Linear 0.1% or Nonlinear 0.0ldBm
Operating Temperature((°C)	-10-+60
Storage Temperature(°C)	-25~+70
Auto-off Time (min)	10
Operating fime(h)	≥130
Battery	3 AA1.5V
Weight (g)	200
Dimensions(mm)	152X74X26







Cut angel	≤80°
life of blade	≥3500
Size	56*56*43mm
	70g
Weight	98g with box